

## KING GEORGE

| Pattern | Construction       | Profile           | Profile     | Edge         | Installation |
|---------|--------------------|-------------------|-------------|--------------|--------------|
| Planks  | Solid / Engineered | Tongue and Groove | Micro Bevel | Hard Wax Oil | Glue         |

### Solid

|                          |  |
|--------------------------|--|
| <b>Overall Thickness</b> | 20mm   |
| <b>Width</b>             | 160, 185, 220mm                              |
| <b>Length</b>            | 600mm-2450mm / 80% of boards will be 1800mm+ |

### Engineered

|                           |  |
|---------------------------|--|
| <b>Overall Thickness</b>  | 16mm (4/12) / 21mm (6/15)                    |
| <b>Width</b>              | 185, 220, 240, 260mm                         |
| <b>Length</b>             | 600mm-2450mm / 80% of boards will be 1800mm+ |
| <b>Underfloor Heating</b> | Yes  |

N.B. Sizes may change at any time

## Grading

|                                     |   |
|-------------------------------------|---|
| <b>Species</b>                      | European Oak (Quercus Robur)                          |
| <b>Top Layer</b>                    | Europe  |
| <b>Base Layer</b>                   | Russia (Betula-Birch)                                 |
| <b>Grade</b>                        | A/B   |
| <b>Maximum Open Filled Knots</b>    | 40mm  |
| <b>Maximum Size of Closed Knots</b> | 60mm  |
| <b>Filled Defects</b>               | Allowed   |
| <b>Sapwood</b>                      | Traces permitted 60mm                                 |
| <b>End Checks</b>                   | No longer than width of board allowed (max. 2mm open) |
| <b>Filler</b>                       | 2 component solvent free filler with oak dust         |
| <b>Colour Variation</b>             | Medium  |
| <b>Filled Crack</b>                 | Allowed   |

## Tests

|                                 |    |
|---------------------------------|----|
| <b>Euro Fire Classification</b> | D3 |
|---------------------------------|----|






## Sustainability & Certifications

| FSC and PEF | Timber Neutral | EUTR              | LACEY ACT         | Formaldehyde Emission                                     |
|-------------|----------------|-------------------|-------------------|---|
| No          | Yes            | Legally Harvested | Legally Harvested | E1 (0.1ppm): complete compliance with EU safety standards |

N.B. We plant 1 tree per every 10m<sup>2</sup> you buy. Certification comes as standard.



# Mouldings



| Bull Nose  | T Bar   | Ramp  | Stop End   | Square Nosing   |
|--|---|---|--|---|
|  |  |  |  |  |

N.B. For a seamless transition, we can colour-match the selected moulding with this product.

## Staircase

We offer the opportunity to customise stairs to complement or match our wood flooring.

- 1. Stairs and claddings are available in a variety of construction types and styles.
- 2. Stair material is available to match the majority of our wood floors.
- 3. We offer both contemporary and traditional nosing styles.
- 4. Stairs are either constructed using our finest engineered platforms or solid wood. Construction will vary depending on nosing types.



## Guarantees

### Lifetime Structural Guarantee:

The Company's warranty commitment is to provide the retail purchaser quality wood flooring that is free from structural defects in milling for the lifetime of the product, where products have been installed to our guidelines and the site conditions for temperature and humidity are met).

### 20-year Finish Guarantee:

The Company's products are covered under this 20 year finish warranty only when cleaned and maintained per the guidelines set forth for the product colour and coating.

In both cases please refer to the Warranty document received at the time of purchase for full guarantee details and exclusions.